MODEL	2148	3158	4108	4208	4258	4308	4358
GPM	2.0	3.0	4.0	3.5	4.0	3.5	3.8
PSI	1400	1500	1000	2000	2500	3000	3500
HP	2.0	3.0	3.0	5.0	7.5	7.5	10.0
HEAT RISE	85°F	110°F	85°F	95°F	85°F	95°F	90°F

MODEL	5308	8208	8308	108
GPM	4.8	7.5	8.0	100gph
PSI	3000	2000	3000	400
HP	10.0	10.0	20.0	0.75
HEAT RISE	105°F	90°F	85°F	210°F

Call your local distributor or email, sales@alkota.com for a complete specification chart.

GET ROLLING TODAY.

When you need maximum cleaning power where space is tight and open flames are out of the question; turn to Alkota's all electric models. Whether the job site is a manufacturing firm, food processing facility, chemical plant or mining operation, our All electric units will give you the cleaning power you need in a safe flameless package. With a small footprint, rugged construction and none of the smoke or hazard emissions you obtain in gas or oil fired units, these washers keep your operations running clean and safe. They give you the durability and ease of the use only Alkota can deliver.

E	nglish to Metric Conversion
10	gallon/minute = 3.78 liters/minute
11	norsepower = .746 watts
10	0 PSI = 7.03 Kg/cm ²
1 1	oot = .3048 meters
11	nch = 2.54 centimeters
1,	oound = .45359 kilograms

Distributed by:

Action Cleaning Systems Inc. Tyler, TX, 800-522-8466 Dallas, TX, 800-950-6926 Midland, TX, 903-262-0236 Bossier City, LA, 318-752-0102

Amp Requirements				
MODEL	230 VOLT 3 PHASE	460 VOLT 3 PHASE		
108	120	60		
2148	70	35		
3158	130	65		
4108	130	65		
4208	130	65		
4258	140	70		
4308	140	70		
4358	150	75		
5308		100		
8208	998	130		
8308		140		



Alkota Model 8308

FEATURES

- · Belt drive, oil bath pumps, ceramic plungers
- Easy access controls
- Precise chemical metering
- Stainless steel immersion heaters
- Stainless steel float tanks
- Standard temperature control
- Easy grip trigger gun
- All models except 108 available UL approved
- 4308XP Explosion proof is available

ADVANTAGES

- Completely powered by electricity
- No open flames
- Minimal noise
- No smoke or fumes
- Small space requirements
- Wheel kits available



^{*} Gallonage and pressure may vary +/- 5% due to manufacturing tolerances in components. Specifications subject to change without notice.